

SYV-75-7-1 SHANGHAI HANKE WIRE CO., LTD.



应用范围

适用于各类数据、音频、视频、数字程控交换机等传输设备的连接线。

APPLICATIONS

For connection of various data, audio, video transmission devices including digital SPC exchange.

电线结构

单根、多股裸绞合铜丝或镀银铜丝；
PE绝缘，单层或多层编织屏蔽，PVC护套。
室外型采用铝箔绕包加接地线屏蔽，PE护套。

WIRE MAKE-UP

Multi-stranded fine bare copper/silver-coated copper single conductor
PE insulation, single or multi-layer mesh shield, PVC sheath
For outdoor use:
aluminum foil worming plus earth line shield, PE sheath

技术参数

- 温度范围: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$
- 符合标准: GB/T 14864-93
- 导体标准: IEC 60228 1类
- 弯曲半径: 大于 $15 \times$ 电缆外径

TECHNICAL DATA

- Operating Temp.: $-10^{\circ}\text{C} \sim +70^{\circ}\text{C}$
- Governing Std.: GB/T 14864-93
- Conductor Std.: Category 1, IEC 60228
- Bending Radius: More than $15 \times$ wire O.D.

产品型号 Product Model	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
单芯 SYV				
SYV-75-2-1	1/0.34	3.15	3.5	17.0
SYV-75-2-2	1/0.34	3.69	4.1	29.0
SYV-75-2-3	1/0.34	3.87	4.3	37.0
SYV-75-3-1	1/0.50	4.95	5.1	36.0
SYV-75-3-2	1/0.50	5.04	5.6	52.0
SYV-75-3-3	1/0.50	5.67	6.3	73.0
SYV-75-4-1	1/0.60	5.40	6.0	67.0
SYV-75-4-2	1/0.60	6.21	6.9	75.0
SYV-75-5-1	1/0.75	6.39	7.1	69.0
SYV-75-5-2	1/0.75	7.11	7.9	95.0
SYV-75-7-1	7/0.40	9.18	10.2	132
SYV-50-1-1	1/0.25	1.80	2.0	10.5
SYV-50-2-1	1/0.68	3.51	3.9	26.5
SYV-50-3-1	1/0.90	4.59	5.1	42.0
SYV-50-5-1	1/1.40	6.57	7.3	82.5
多芯 SYV				
SYV-75-2-1×2	2×1/0.34	2.97×6.12	3.3×6.8	34.5
SYV-75-2-1×4	4×1/0.34	8.28	9.2	108
SYV-75-2-1×6	6×1/0.34	10.89	11.0	150
SYV-75-2-1×7	7×1/0.34	10.89	11.0	156
SYV-75-2-1×8	8×1/0.34	9.71	11.9	179
SYV-75-2-1×10	10×1/0.34	12.83	14.3	229
SYV-75-2-1×12	12×1/0.34	13.32	14.8	255

(续)

产品型号 Product Model	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
SYV-75-2-1×16	16×1/0.34	14.76	16.4	342
SYV-75-2-2×2	2×1/0.34	3.60×7.38	4.0×8.2	59.0
SYV-75-2-2×4	4×1/0.34	9.81	10.9	163
SYV-75-2-2×6	6×1/0.34	11.88	13.2	232
SYV-75-2-2×7	7×1/0.34	11.88	13.2	243
SYV-75-2-2×8	8×1/0.34	12.78	14.2	288
SYV-75-2-2×10	10×1/0.34	15.84	17.6	371
SYV-75-2-2×12	12×1/0.34	16.47	18.3	425
SYV-75-2-2×16	16×1/0.34	18.00	20.0	557
SYV-75-3-1×2	2×1/0.50	4.50×9.36	5.0×10.4	75.0
SYV-75-3-1×4	4×1/0.50	10.98	12.2	192
SYV-75-3-1×6	6×1/0.50	15.03	16.7	288
SYV-75-3-1×7	7×1/0.50	15.03	16.7	333
SYV-75-3-1×8	8×1/0.50	16.65	18.5	391
SYV-75-3-2×2	2×1/0.50	5.04×9.35	5.6×11.5	114
SYV-75-3-2×4	4×1/0.50	13.77	15.3	282
SYV-75-3-2×6	6×1/0.50	17.01	18.9	421
SYV-75-3-2×7	7×1/0.50	17.01	18.9	475
SYV-75-3-2×8	8×1/0.50	18.18	20.2	536
多芯 SYV (室外型)				
SYV(Y)-75-2-1×8	8×1/0.34	11.34	12.6	195
SYV(Y)-75-2-2×8	8×1/0.34	13.86	15.4	296
SYV(Y)-75-3-1×8	8×1/0.50	17.46	19.4	409
SYV(Y)-75-3-2×8	8×1/0.50	18.99	21.1	566