

SJT 60°C 300V 4 × 14AWG SHHKW



应用范围

适用于小型电动工具等电源线。

APPLICATIONS

For power supply line of small-sized electric tools

电线结构

多股细裸束绞铜丝或镀锡铜丝导体；
PVC绝缘，PVC护套；
SJTW为户外型。

WIRE MAKE-UP

Multi-stranded bare copper/tincopper conductor
PVC insulation, PVC sheath
SJTW is for outdoor use.

技术参数

☑ 温度范围：60°C(用户需要可生产75、90、105°C等级)
☑ 额定电压：300V
☑ 符合标准：UL 62

TECHNICAL DATA

☑ Operating Temp.: 60°C(75, 90, 105°C products also available at your request)
☑ Rated Voltage: 600V
☑ Governing Std.: UL 62

规格 Size 芯数 × AWG Core No. × AWG	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
2 × 18	2 × 41/0.16	7.47	8.0	73.8
2 × 16	2 × 26/0.254	8.03	8.6	90.7
2 × 14	2 × 41/0.254	8.97	9.5	110
2 × 12	2 × 65/0.254	10.57	11.6	174
2 × 10	2 × 65/0.32	14.79	15.4	319
3 × 18	3 × 41/0.16	7.91	8.5	86.7
3 × 16	3 × 26/0.254	8.52	9.1	109
3 × 14	3 × 41/0.254	9.53	10.0	144
3 × 12	3 × 65/0.254	11.19	12.1	212
3 × 10	3 × 65/0.32	15.68	16.1	383
4 × 18	4 × 41/0.16	8.66	9.3	104
4 × 16	4 × 26/0.254	9.34	10.0	132
4 × 14	4 × 41/0.254	10.47	11.1	176
4 × 12	4 × 65/0.254	12.25	13.2	260
4 × 10	4 × 65/0.32	17.18	17.8	466
5 × 18	5 × 41/0.16	9.49	9.9	123
5 × 16	5 × 26/0.254	10.24	10.9	156
5 × 14	5 × 41/0.254	11.51	12.4	210
5 × 12	5 × 65/0.254	13.41	14.4	309
5 × 10	5 × 65/0.32	18.84	19.4	553